

# Showcases



# Showcases

**QUALITY** Standing in Time

**SUSTAINABILITY** Respecting Nature

Guided by experience, arriving for performance, the showcase range is composed of three models of elegant design, high quality and functionality. The tempered glasses as well as the stainless steel extra shining finiture, are some of the features that ensure a vivid and attractive display.

## V-MODELS Technical Characteristics

- Constructed completely in stainless steel AISI 304 18/10.
- All points of contact are double bended, ensuring maximum safety
- Ventilated air circulation for uniform temperature
- New generation electronic touch screen thermostat with energy saving features and night mode.
- Led lighting and tempered glass
- Stainless steel adjustable feet for maximum hygiene and stability, or floor skirting upon request.



### Refrigerated Models

- Low energy consumption L'Unite Tecumseh compressor, suitable for tropical climates
- Copper tube condenser with painted aluminum fins to ensure maximum life duration
- Adaptive defrost management and automatic water evaporation.
- High quality fans
- Refrigerant liquids by Linde
- Two stages leakage test by high pressure Nitrogen



## Showcases Line VS With Straight Glass Display and Shelf



Model	Temperature	Power	Dimensions (cm.)
Refrigerated Ventilated Showcase			
VS-R2	+2/+8° C	0.66 KW/230V	85x75x125
VS-R3	+2/+8° C	0.88 KW/230V	117.5x75x125
VS-R4	+2/+8° C	0.98 KW/230V	150x75x125
VS-R5	+2/+8° C	1.02 KW/230V	182.5x75x125
Heated Ventilated Showcase			
VS-H2	+65/+90° C	1.31 KW/230V	85x75x125
VS-H3	+65/+90° C	1.32 KW/230V	117.5x75x125
VS-H4	+65/+90° C	2.02 KW/230V	150x75x125
VS-H5	+65/+90° C	2.03 KW/230V	182.5x75x125
Neutral Showcase			
VS-N2	-	0.01 KW/230V	85x75x125
VS-N3	-	0.02 KW/230V	117.5x75x125
VS-N4	-	0.02 KW/230V	150x75x125
VS-N5	-	0.03 KW/230V	182.5x75x125

## Showcases Line VL With Straight Glass Display and two Sheves



Model	Temperature	Power	Dimensions (cm.)
Refrigerated Ventilated Showcase			
VS-R2	+2/+8° C	0.66 KW/230V	85x75x137
VS-R3	+2/+8° C	0.88 KW/230V	117.5x75x137
VS-R4	+2/+8° C	0.98 KW/230V	150x75x137
VS-R5	+2/+8° C	1.02 KW/230V	182.5x75x137
Heated Ventilated Showcase			
VS-H2	+65/+90° C	1.31 KW/230V	85x75x137
VS-H3	+65/+90° C	1.32 KW/230V	117.5x75x137
VS-H4	+65/+90° C	2.02 KW/230V	150x75x137
VS-H5	+65/+90° C	2.03 KW/230V	182.5x75x137
Neutral Showcase			
VS-N2	-	0.01 KW/230V	85x75x137
VS-N3	-	0.02 KW/230V	117.5x75x137
VS-N4	-	0.02 KW/230V	150x75x137
VS-N5	-	0.03 KW/230V	182.5x75x137

## Showcases Line VP With Straight Parallel Glass Display



Model	Temperature	Power	Dimensions (cm.)
Refrigerated Ventilated Showcase			
VS-R2	+2/+8° C	0.66 KW/230V	85x75x120
VS-R3	+2/+8° C	0.88 KW/230V	117.5x75x120
VS-R4	+2/+8° C	0.98 KW/230V	150x75x120
VS-R5	+2/+8° C	1.02 KW/230V	182.5x75x120
Heated Ventilated Showcase			
VS-H2	+65/+90° C	1.31 KW/230V	85x75x120
VS-H3	+65/+90° C	1.32 KW/230V	117.5x75x120
VS-H4	+65/+90° C	2.02 KW/230V	150x75x120
VS-H5	+65/+90° C	2.03 KW/230V	182.5x75x120
Neutral Showcase			
VS-N2	-	0.01 KW/230V	85x75x120
VS-N3	-	0.02 KW/230V	117.5x75x120
VS-N4	-	0.02 KW/230V	150x75x120
VS-N5	-	0.03 KW/230V	182.5x75x120

**HYGIENE & SAFETY** The Cornerstone of Every Kitchen

**DESIGN** Industrial Elegance



## **Bountourakis S.A.**

C street, 1A, 71601  
Heraklion Industrial Area,  
Crete, Greece

T: 2810 380991

F: 2810 380992

[info@bountourakis.com](mailto:info@bountourakis.com)

[www.bountourakis.com](http://www.bountourakis.com)

